



SEARCH

UTILITY LOCATORS

PIPE & CABLE


- 910R
- 910T
- 970T
- 950R/T
- 830R/T
- 150R/T
- 250R/T

- CABLE FAULT
- PLASTIC PIPE & DUCT

950R/T LOCATING EQUIPMENT

The 950R/T electronic locating system is the quickest way to locate buried telephone, CATV, power, gas and water lines. In active mode, the 950T transmits via direct-line connection, induction clamp or induced broadcast signals. In passive mode, the 950R receiver detects signals generated by 31 kHz (CATV) and 50/60 Hz power, as well as re-radiated radio frequencies. And in beacon mode, the 950R detects signals from optional beacons to locate non-metallic service lines.

- FIND YOUR DEALER
- REQUEST INFO



- KEY FEATURES
- DETAILS
- LITERATURE
- MANUAL
- OFFERS



KEY FEATURES, 950R/T

- Lightweight 950R receiver is balanced for easy handling.
- 950R/T offers simultaneous 8 and 29 kHz transmission, so an alternate signal is available if one is hard to detect; 80 kHz frequency is helpful in locating old tracer wires and pipes with insulators.

- SPECS
- SAFETY
- JOB RELATED

SPECIFICATIONS, 950R/T

PRINT

950R RECEIVER

RECEIVER DIMENSIONS

	U.S.	METRIC
Height	27.75 in	705 mm
Length	12.8 in	325 mm
Width	5.9 in	145 mm
Operating weight	4.5 lb	2 kg

RECEIVER OPERATION

	U.S.	METRIC
Operating temperature range	-4° F to 122° F	-20° C to 50° C
Antenna configurations:	Single peak, twin peak, null, left/right (line only)	
Audio output:	Speaker	
Depth estimate tolerances*		
Active line ± 3%	0.2 ft - 5 ft	0.06 m - 1.5 m
Active line ± 5%	5 ft - 10 ft	1.5 m - 3 m
Active line ± 10%	10 ft and deeper	3 m and deeper
Passive line ± 10%	0.5 ft - 10 ft	1.5 m - 3 m
Beacon ± 5%	0.5 ft - 10 ft	1.5 m - 3 m

LCD Backlight: LED (green)
External ports: RS-232 serial

RECEIVER BATTERIES

Type: 6 C-cell alkaline

Battery life: Approximately 50 hours (continuous use at 70° F/21° C)

Battery saver: Unit shuts off after 5 minutes of inactivity

950T TRANSMITTER

TRANSMITTER DIMENSIONS

	U.S.	METRIC
Height	11 in	280 mm
Length	14 in	355 mm
Width	4.2 in	107 mm
Operating weight	7.25 lb	3.3 kg

TRANSMITTER OPERATION

	U.S.	METRIC
Operating temperature range	-4° F to 122° F	-20° C to 50° C
Maximum power output: 3 Watts		
Operating modes: 512 Hz, 1 kHz, 8 kHz, and dual (8 kHz and 29 kHz)		
Timer: Unit runs continuously or shuts off after running for selected hour interval (8-hour maximum)		

TRANSMITTER BATTERIES

Type: 8 D-cell alkaline

Battery life: Approximately 40 hours (continuous use at power level 2)

OPERATIONAL FREQUENCIES

Passive (standard): 50 Hz, 60 Hz, radio

Passive (optional): 50 P power, 60 P power, 100 Hz, 120 Hz, 31 kHz

Active (standard): 512 Hz, 1 kHz, 8 kHz, 29 kHz, 80 kHz, 33 kHz (EML)

Active other (optional): 400 Hz, 560 Hz, 815 Hz, 200 kHz

Beacon (non-roll) 512 Hz, 29 kHz, 33kHz



1959 W. Fir St.
Perry, OK 73077-5803

Toll free: 800-654-6481
Fax: 580-336-3458

OUR COMPANY

About Us
Find A Dealer
Request Info
Press Room
Careers
Contact Us

QUICK LINKS

Current Offers
Used Equipment
Selector Tools
Operator Manuals
Videos
Trailers

POPULAR PRODUCTS

RT115 Quad
FX25
SK650
830R/T
JT4020 All Terrain
RT45

CATEGORIES

All Terrain Drills
Downhole Tools
Pipe & Cable Locators
Vac Excavation Options
OnGrade Drilling
Compact Tool Carriers

CONNECT

